RECEIVING HOPPERS

High-capacity product receiving and cleaning







- → Capacity of up to 170 tons/hour
- → Fast discharge of products
- Continuous feed to processing line
- Side and rear loading



Tolsma-Grisnich B.V.

Fabrieksweg 7, 8304 AT Emmeloord, The Netherlands T +31 (0)527 63 64 65 • E info@tolsmagrisnich.com

CONTINUOUS FEEDING

The speedy unloading of trucks is key to the reception of bulk products. This means that the receiving hopper needs to combine a high processing capacity with a substantial buffering capacity. Tolsma-Grisnich receiving hoppers combine a capacity of up to 170 tons/hr with an impressive buffer, so that an uninterrupted product supply to the processing line is guaranteed.


CUSTOM-BUILT

Tolsma-Grisnich receiving hoppers are generally custom-built. In addition to capacity and type of basal matting, the following features are taken into account according to customer requirements:

- fold-away side panels for container doors
- · hydraulic height adjustment for side and rear bulkheads
- easy to operate control box
- connections for L/H and R/H lower discharge trailers
- manually height-adjustable intake-access bulkhead
- · flow control
- dosing reel
- · integrated sampling

PRODUCT CLEANING

The Tolsma-Grisnich receiving hoppers can be coupled to a cleaning unit that separates loose soil, clods and haulm from the product. Several product-friendly techniques (star-type, spiral or roller cleaners and sieve conveyors) are available.







Subject to changes in construction and implementation and printing errors.



Tolsma-Grisnich B.V.

Fabrieksweg 7, 8304 AT Emmeloord, The Netherlands T +31 (0)527 63 64 65 • E info@tolsmagrisnich.com